

CS-C1C-D0-1D2WFR

1080P Indoor Internet Wi-Fi Camera



Introduction

EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ, you can talk to your loved ones, watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.

Main Features



FHD 1080P



130° Wide-Angle Lens



True Day/Night, auto switch, Infra-Red support up to 12meters(39.37ft)



Two-way audio



Support Micro SD card (Max. 256G)



Support 2.4GHz Wi-Fi (IEEE802.11b, 802.11g,802.11n)

Dimension



Specifications

Model	CS-C1C-D0-1D2WFR
Camera	
Image sensor	1/2. 9" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	2.8mm, view angle:106° (Horizontal), 130°(Diagonal)
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR
Compression	
Video Compression	H.264
H.264 Type	Main Profile
Video Bit Rate	Ultra-HD; HD; Standard. Adaptive bit rate.
Audio Bit Rate	Self-Adaptive
Max. Bitrate	2M
Image	
Max. Resolution	1920 × 1080
Frame Rate	Max: 20fps; Self-Adaptive during network transmission
Network	
Smart Alarm	Motion detection
Wi-Fi Pairing	AP paring
Protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image, Password Protection, Watermark
Interface	
Storage	Micro SD card slot (Max. 256G)
Power	Micro USB
Wi-Fi	
Standard	IEEE802.11b, 802.11g, 802.11n Draft
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Support 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps,11g :54Mbps,11n :72Mbps
General	
Operating Conditions	14°F to 113 °F (-10°C ~ 45°C), Humidity 95% or less (non-condensing)
Power Supply	DC 5V±10%
Power Consumption	MAX. 4.0 W
IR Range	MAX. 12 meters(39.37ft)
Dimensions	64mm x 64mm x 103mm(2.52 " x 2.52 " x 4.06 ")
Packaging Dimensions	123mm x 79mm x 125.5mm(4.84 " x 3.11 " x 4.94 ")
Suttle Weight	96g(0.21lbs)